



WIRELESS CHARGER BSA2

Inductive Charging Stand

Technical details

LED display:	Yes
Output:	5W I 7,5W I 10W I 15W (depending on the device being charged)
Input:	USB-C
Qi-Version:	Version 1.2.4
Frequenzy band:	110 - 205 kHz
Max. radiated transmitting power:	15 watt
Current consumption: (compatible power supplies)	9V-2A, 12V-1.5A, PD 3.0, QC 3.0 quick charge power supply
Properties:	Overvoltage protection, overheat protection, foreign object detec-
	tion, plastic smartphone cases up to 5 mm usually do not impede the charging process, use during the charging process horizontally and vertically possible
Accessories:	to 5 mm usually do not impede the charging process, use during the charging process horizontally and
Accessories: Dimensions:	to 5 mm usually do not impede the charging process, use during the charging process horizontally and vertically possible USB-A to USB-A charging cable (1,5m),
	to 5 mm usually do not impede the charging process, use during the charging process horizontally and vertically possible USB-A to USB-A charging cable (1,5m), Power Delivery Adapter (20W)
Dimensions:	to 5 mm usually do not impede the charging process, use during the charging process horizontally and vertically possible USB-A to USB-A charging cable (1,5m), Power Delivery Adapter (20W) 70 x 70 x 110mm

Article data

Соlоиг	Article number	EAN
Black	7410620	4 034303 032587

