



POWER ADAPTER W40CC GaN

Fast Charger

Technical Information

Colour:	White
Surface:	Plastic
Input connector:	EU connector
Input voltage:	100 - 240 V
Input alternating current frequency:	50 / 60 Hz
Connections:	USB-C 1, USB-C 2
Output:	Supports (downwards compatible) PD 3.0, PPS and QC 4.0 USB-C 1/2: 5.0 V/DC 3.0 A, max. 15.0 W 9.0 V/DC 3.0 A, max. 27.0 W 12.0 V/DC 3.0 A, max. 36.0 W 15.0 V/DC 2.67 A, max. 40.0 W 20.0 V/DC 2.0 A, max. 40.0 W PPS: 3.3 – 11.0 V/DC 3.0 A, max. 40.0 W 3.3 – 21.0 V/DC 2.0 A, max. 40.0 W USB-C 1 + USB-C 2: USB-C 1: 5.0 V/DC 3.0 A, max. 15.0 W 9.0 V/DC 2.22 A, max. 20.0 W USB-C 2: 5.0 V/DC 3.0 A, max. 15.0 W 9.0 V/DC 2.22 A, max. 20.0 W Total: max. 40.0 W
Average efficiency:	88.57 %
Efficiency at low load (10 %):	78.02 %

Power consumption at no load:	0.12 W
Dimensions:	35.8 x 35.4 x 91.4 mm
Weight:	80.8 g
Packing unit:	2pcs

Product data

Colour	Article number	EAN
White	7804012	4 034303 033348



What is GaN?

GaN adapters are a new type of power adapter that offers numerous advantages over conventional silicon-based adapters. GaN stands for gallium nitride, a material with a higher power density.

The use of GaN enables smaller power adapters that can handle higher voltages and currents while generating less heat. This makes the technology particularly suitable for powerful USB chargers with multiple ports.